

SOPORTES ELÁSTICOS**SOPORTE CAUCHO-METAL**LC

| | REF / ART.NR | DIMENSIONES | | | | | | | | | | | CARGA ESTÁTICA | | RELACIÓN RIGIDEZ | | | |
|-----------|--------------|-------------|-----|------|------|-----|------|------|------|------|-----|-----|----------------|---------|------------------|-----|-----|-----|
| | | Sh | ØA | B | ØD | C | e | ØF | ØG | H | I | J | ØK | CARGA | FLECHA | Kx | Ky | Kz |
| | | mm. | | | | | | | | | | | kg. | mm. | | | | |
| LC | LC102NR35 | 35 | 66 | 45 | 10.3 | 12 | 2.5 | 25.5 | 12.8 | 82.5 | 102 | 70 | 57 | 50 | 3,5±0,5 | 1 | 1,1 | 1,9 |
| | LC102NR45 | 45 | 66 | 45 | 10.3 | 12 | 2.5 | 25.5 | 12.8 | 82.5 | 102 | 70 | 57 | 80 | 3,5±0,5 | 1 | 1,1 | 1,9 |
| | LC102NR55 | 55 | 66 | 45 | 10.3 | 12 | 2.5 | 25.5 | 12.8 | 82.5 | 102 | 70 | 57 | 120 | 3,5±0,5 | 1 | 1,1 | 1,9 |
| | LC102NR65 | 65 | 66 | 45 | 10.3 | 12 | 2.5 | 25.5 | 12.8 | 82.5 | 102 | 70 | 57 | 170 | 3,5±0,5 | 1 | 1,1 | 1,9 |
| | LC102NR75 | 75 | 66 | 45 | 10.3 | 12 | 2.5 | 25.5 | 12.8 | 82.5 | 102 | 70 | 57 | 215 | 3,5±0,5 | 1 | 1,1 | 1,9 |
| | LC122NR35 | 35 | 70 | 50 | 10.4 | 16 | 3 | 25.5 | 12.8 | 100 | 122 | 75 | 57 | 95 | 4,5±0,5 | 1 | 1,1 | 1,9 |
| | LC122NR45 | 45 | 70 | 50 | 10.4 | 16 | 3 | 25.5 | 12.8 | 100 | 122 | 75 | 57 | 125 | 4,5±0,5 | 1 | 1,1 | 1,9 |
| | LC122NR55 | 55 | 70 | 50 | 10.4 | 16 | 3 | 25.5 | 12.8 | 100 | 122 | 75 | 57 | 150 | 4,5±0,5 | 1 | 1,1 | 1,9 |
| | LC122NR65 | 65 | 70 | 50 | 10.4 | 16 | 3 | 25.5 | 12.8 | 100 | 122 | 75 | 57 | 260 | 4,5±0,5 | 1 | 1,1 | 1,9 |
| | LC122NR75 | 75 | 70 | 50 | 10.4 | 16 | 3 | 25.5 | 12.8 | 100 | 122 | 75 | 57 | 375 | 4,5±0,5 | 1 | 1,1 | 1,9 |
| | LC170NR35 | 35 | 95 | 70 | 13 | 18 | 3 | 34 | 22 | 141 | 170 | 100 | 74 | 180 | 6,0±1,0 | 1 | 1,1 | 1,9 |
| | LC170NR45 | 45 | 95 | 70 | 13 | 18 | 3 | 34 | 22 | 141 | 170 | 100 | 74 | 240 | 6,0±1,0 | 1 | 1,1 | 1,9 |
| | LC170NR55 | 55 | 95 | 70 | 13 | 18 | 3 | 34 | 22 | 141 | 170 | 100 | 74 | 350 | 6,0±1,0 | 1 | 1,1 | 1,9 |
| | LC170NR65 | 65 | 95 | 70 | 13 | 18 | 3 | 34 | 22 | 141 | 170 | 100 | 74 | 540 | 6,0±1,0 | 1 | 1,1 | 1,9 |
| | LC170NR75 | 75 | 95 | 70 | 13 | 18 | 3 | 34 | 22 | 141 | 170 | 100 | 74 | 700 | 6,0±1,0 | 1 | 1,1 | 1,9 |
| | LC302NR35 | 35 | 66 | 45 | 10.3 | 12 | 2.5 | 25.5 | 12.8 | 82.5 | 102 | 70 | 57 | 55 | 3,5±0,5 | 1 | 1,9 | 1,9 |
| | LC302NR45 | 45 | 66 | 45 | 10.3 | 12 | 2.5 | 25.5 | 12.8 | 82.5 | 102 | 70 | 57 | 100 | 3,5±0,5 | 1 | 1,9 | 1,9 |
| | LC302NR55 | 55 | 66 | 45 | 10.3 | 12 | 2.5 | 25.5 | 12.8 | 82.5 | 102 | 70 | 57 | 140 | 3,5±0,5 | 1 | 1,9 | 1,9 |
| LC302NR65 | 65 | 66 | 45 | 10.3 | 12 | 2.5 | 25.5 | 12.8 | 82.5 | 102 | 70 | 57 | 180 | 3,5±0,5 | 1 | 1,9 | 1,9 | |
| LC302NR75 | 75 | 66 | 45 | 10.3 | 12 | 2.5 | 25.5 | 12.8 | 82.5 | 102 | 70 | 57 | 350 | 3,5±0,5 | 1 | 1,9 | 1,9 | |
| AC | REF / ART.NR | DIMENSIONES | | | | | | | | | | | | | | | | |
| | | ØA | B | e | ØG | | | | | | | | | | | | | |
| | | mm. | | | | | | | | | | | | | | | | |
| AC | AC102 | 60 | 8 | 5 | 13 | | | | | | | | | | | | | |
| | AC170 | 75 | 8 | 5 | 21 | | | | | | | | | | | | | |
| AR | AR102 | 47 | 6.5 | . | 13 | | | | | | | | | | | | | |
| | AR170 | 62 | 7 | . | 23 | | | | | | | | | | | | | |

