

R80TAS_DE

| | REF / ART.NR | ABMESSUNGEN | | | | | | DRUCKBELASTUNG | |
|----------------|--------------|-------------|----|------|-----|----------------|----------|----------------|----------|
| | | TUBOØ | A | H | L | M | R | LAST | FEDERWEG |
| | mm. | | | | | | kg. | mm. | |
| R80T | R80T30EPDM50 | 30 | 28 | 73 | 55 | M-08 | 15,0 | 33 | 2,8±0,5 |
| | R80T35EPDM50 | 35 | 28 | 70 | 56 | M-08 | 17,5 | 26 | 2,2±0,5 |
| HÄRTE 50 SHÖRE | | | | | | | | | |
| | REF / ART.NR | ABMESSUNGEN | | | | DRUCKBELASTUNG | | | |
| | | ØA | B | D | C | LAST | FEDERWEG | | |
| | mm. | | | | kg. | mm. | | | |
| AS | AS29 | 30 | 10 | M-08 | 20 | 60 | 1,5±0,5 | | |
| | AS39 | 40 | 15 | M-10 | 25 | 60 | 2,0±0,5 | | |
| | AS40 | 40 | 25 | M-10 | 25 | 90 | 4,0±0,5 | | |
| | AS55 | 55 | 30 | M-10 | 50 | 150 | 4,5±0,5 | | |
| HÄRTE 60 SHÖRE | | | | | | | | | |

AS29

AS39

AS40-55

R80T

