

|                | REF / ART.NR | ABMESSUNGEN |      |      |      | DRUCKBELASTUNG |          |
|----------------|--------------|-------------|------|------|------|----------------|----------|
|                |              | ØA          | B    | D    | C    | LAST           | FEDERWEG |
|                | mm.          |             |      |      |      |                | kg.      |
| <b>S</b>       | 0 0 0        | 40          | 23   | M-08 | 55   | 60             | 3,5±0,5  |
|                | 0 0          | 60          | 28   | M-10 | 80   | 160            | 4,0±1,0  |
|                | 0            | 70          | 32   | M-12 | 100  | 300            | 4,5±1,0  |
|                | 1            | 85          | 30   | M-12 | 100  | 500            | 4,5±1,0  |
|                | 2            | 100         | 40   | M-14 | 110  | 600            | 6,0±1,0  |
|                | 3            | 120         | 50   | M-16 | 120  | 900            | 7,5±1,0  |
|                | 4            | 140         | 50   | M-16 | 120  | 1200           | 8,0±1,0  |
|                | 5            | 160         | 60   | M-16 | 120  | 1750           | 9,0±1,0  |
| 6              | 180          | 70          | M-24 | 136  | 2500 | 11,0±1,5       |          |
| 7              | 205          | 75          | M-24 | 136  | 3500 | 12,0±2,0       |          |
| HÄRTE 60 SHÖRE |              |             |      |      |      |                |          |
| <b>S-B</b>     | 00B          | 60          | 18   | M-10 | 80   | 200            | 2,0±0,5  |
|                | 0B           | 70          | 20   | M-12 | 100  | 350            | 2,0±0,5  |
|                | 1B           | 85          | 25   | M-12 | 100  | 600            | 2,2±0,5  |
|                | 2B           | 100         | 20   | M-14 | 110  | 800            | 2,5±0,5  |
|                | 3B           | 120         | 25   | M-16 | 120  | 1100           | 2,5±0,5  |
|                | 4B           | 140         | 33   | M-16 | 120  | 2000           | 3,5±0,5  |
|                | 5B           | 160         | 31   | M-16 | 120  | 3000           | 4,0±1,0  |
| HÄRTE 75 SHÖRE |              |             |      |      |      |                |          |
| <b>AS</b>      | AS4020-60SH  | 40          | 20   | M-08 | 40   | 90             | 4,0±0,5  |
|                | AS5020-45SH  | 52          | 20   | M-10 | 70   | 180            | 4,0±1,0  |
|                | AS6020-60SH  | 52          | 20   | M-10 | 70   | 275            | 4,0±1,0  |
|                | AS6520-75SH  | 52          | 20   | M-12 | 90   | 750            | 4,0±1,0  |
|                | AS7526-60SH  | 69          | 26   | M-12 | 80   | 330            | 5,0±1,0  |
|                | AS8026-75SH  | 69          | 26   | M-12 | 80   | 550            | 5,0±1,0  |

