

|                | REF / ART.NR | ABMESSUNGEN |    |      |     | DRUCKBELASTUNG |          |
|----------------|--------------|-------------|----|------|-----|----------------|----------|
|                |              | ØA          | B  | D    | C   | LAST           | FEDERWEG |
|                | mm.          |             |    |      |     |                | kg.      |
| <b>S</b>       | 0 0 0        | 40          | 23 | M-08 | 55  | 60             | 3,5±0,5  |
|                | 0 0          | 60          | 28 | M-10 | 80  | 160            | 4,0±1,0  |
|                | 0            | 70          | 32 | M-12 | 100 | 300            | 4,5±1,0  |
|                | 1            | 85          | 30 | M-12 | 100 | 500            | 4,5±1,0  |
|                | 2            | 100         | 40 | M-14 | 110 | 600            | 6,0±1,0  |
|                | 3            | 120         | 50 | M-16 | 120 | 900            | 7,5±1,0  |
|                | 4            | 140         | 50 | M-16 | 120 | 1200           | 8,0±1,0  |
|                | 5            | 160         | 60 | M-16 | 120 | 1750           | 9,0±1,0  |
|                | 6            | 180         | 70 | M-24 | 136 | 2500           | 11,0±1,5 |
|                | 7            | 205         | 75 | M-24 | 136 | 3500           | 12,0±2,0 |
| HÄRTE 60 SHÖRE |              |             |    |      |     |                |          |
| <b>S-B</b>     | 00B          | 60          | 18 | M-10 | 80  | 200            | 2,0±0,5  |
|                | 0B           | 70          | 20 | M-12 | 100 | 350            | 2,0±0,5  |
|                | 1B           | 85          | 25 | M-12 | 100 | 600            | 2,2±0,5  |
|                | 2B           | 100         | 20 | M-14 | 110 | 800            | 2,5±0,5  |
|                | 3B           | 120         | 25 | M-16 | 120 | 1100           | 2,5±0,5  |
|                | 4B           | 140         | 33 | M-16 | 120 | 2000           | 3,5±0,5  |
|                | 5B           | 160         | 31 | M-16 | 120 | 3000           | 4,0±1,0  |
| HÄRTE 75 SHÖRE |              |             |    |      |     |                |          |
| <b>AS</b>      | AS4020-60SH  | 40          | 20 | M-08 | 40  | 90             | 4,0±0,5  |
|                | AS5020-45SH  | 52          | 20 | M-10 | 70  | 180            | 4,0±1,0  |
|                | AS6020-60SH  | 52          | 20 | M-10 | 70  | 275            | 4,0±1,0  |
|                | AS6520-75SH  | 52          | 20 | M-12 | 90  | 750            | 4,0±1,0  |
|                | AS7526-60SH  | 69          | 26 | M-12 | 80  | 330            | 5,0±1,0  |
|                | AS8026-75SH  | 69          | 26 | M-12 | 80  | 550            | 5,0±1,0  |

