

SSBAS_EU

	REF / ART.NR	DIMENTSIOAK				KONPRESIOA	
		ØA	B	D	C	KARGA	GEZI
	mm.						kg.
S	0 0 0	40	23	M-08	55	60	3,5±0,5
	0 0	60	28	M-10	80	160	4,0±1,0
	0	70	32	M-12	100	300	4,5±1,0
	1	85	30	M-12	100	500	4,5±1,0
	2	100	40	M-14	110	600	6,0±1,0
	3	120	50	M-16	120	900	7,5±1,0
	4	140	50	M-16	120	1200	8,0±1,0
	5	160	60	M-16	120	1750	9,0±1,0
	6	180	70	M-24	136	2500	11,0±1,5
	7	205	75	M-24	136	3500	12,0±2,0
GOGORTASUNA 60 SHÖRE							
S-B	00B	60	18	M-10	80	200	2,0±0,5
	0B	70	20	M-12	100	350	2,0±0,5
	1B	85	25	M-12	100	600	2,2±0,5
	2B	100	20	M-14	110	800	2,5±0,5
	3B	120	25	M-16	120	1100	2,5±0,5
	4B	140	33	M-16	120	2000	3,5±0,5
	5B	160	31	M-16	120	3000	4,0±1,0
GOGORTASUNA 75 SHÖRE							
AS	AS4020-60SH	40	20	M-08	40	90	4,0±0,5
	AS5020-45SH	52	20	M-10	70	180	4,0±1,0
	AS6020-60SH	52	20	M-10	70	275	4,0±1,0
	AS6520-75SH	52	20	M-12	90	750	4,0±1,0
	AS7526-60SH	69	26	M-12	80	330	5,0±1,0
	AS8026-75SH	69	26	M-12	80	550	5,0±1,0

