

| | REF / ART.NR | DIMENSIONS | | | | COMPRESSION | |
|-----------------|--------------|------------|----|------|-----|-------------|----------|
| | | ØA | B | D | C | CHARGE | FLECHE |
| | | mm. | | | | kg. | mm. |
| S | 0 0 0 | 40 | 23 | M-08 | 55 | 60 | 3,5±0,5 |
| | 0 0 | 60 | 28 | M-10 | 80 | 160 | 4,0±1,0 |
| | 0 | 70 | 32 | M-12 | 100 | 300 | 4,5±1,0 |
| | 1 | 85 | 30 | M-12 | 100 | 500 | 4,5±1,0 |
| | 2 | 100 | 40 | M-14 | 110 | 600 | 6,0±1,0 |
| | 3 | 120 | 50 | M-16 | 120 | 900 | 7,5±1,0 |
| | 4 | 140 | 50 | M-16 | 120 | 1200 | 8,0±1,0 |
| | 5 | 160 | 60 | M-16 | 120 | 1750 | 9,0±1,0 |
| | 6 | 180 | 70 | M-24 | 136 | 2500 | 11,0±1,5 |
| | 7 | 205 | 75 | M-24 | 136 | 3500 | 12,0±2,0 |
| DURETE 60 SHORE | | | | | | | |
| S-B | 00B | 60 | 18 | M-10 | 80 | 200 | 2,0±0,5 |
| | 0B | 70 | 20 | M-12 | 100 | 350 | 2,0±0,5 |
| | 1B | 85 | 25 | M-12 | 100 | 600 | 2,2±0,5 |
| | 2B | 100 | 20 | M-14 | 110 | 800 | 2,5±0,5 |
| | 3B | 120 | 25 | M-16 | 120 | 1100 | 2,5±0,5 |
| | 4B | 140 | 33 | M-16 | 120 | 2000 | 3,5±0,5 |
| | 5B | 160 | 31 | M-16 | 120 | 3000 | 4,0±1,0 |
| DURETE 75 SHORE | | | | | | | |
| AS | AS4020-60SH | 40 | 20 | M-08 | 40 | 90 | 4,0±0,5 |
| | AS5020-45SH | 52 | 20 | M-10 | 70 | 180 | 4,0±1,0 |
| | AS6020-60SH | 52 | 20 | M-10 | 70 | 275 | 4,0±1,0 |
| | AS6520-75SH | 52 | 20 | M-12 | 90 | 750 | 4,0±1,0 |
| | AS7526-60SH | 69 | 26 | M-12 | 80 | 330 | 5,0±1,0 |
| | AS8026-75SH | 69 | 26 | M-12 | 80 | 550 | 5,0±1,0 |

