

SSBAS\_FR

|                 | REF / ART.NR | DIMENSIONS |    |      |     | COMPRESSION |          |
|-----------------|--------------|------------|----|------|-----|-------------|----------|
|                 |              | ØA         | B  | D    | C   | CHARGE      | FLECHE   |
|                 |              | mm.        |    |      |     | kg.         | mm.      |
| <b>S</b>        | 0 0 0        | 40         | 23 | M-08 | 55  | 60          | 3,5±0,5  |
|                 | 0 0          | 60         | 28 | M-10 | 80  | 160         | 4,0±1,0  |
|                 | 0            | 70         | 32 | M-12 | 100 | 300         | 4,5±1,0  |
|                 | 1            | 85         | 30 | M-12 | 100 | 500         | 4,5±1,0  |
|                 | 2            | 100        | 40 | M-14 | 110 | 600         | 6,0±1,0  |
|                 | 3            | 120        | 50 | M-16 | 120 | 900         | 7,5±1,0  |
|                 | 4            | 140        | 50 | M-16 | 120 | 1200        | 8,0±1,0  |
|                 | 5            | 160        | 60 | M-16 | 120 | 1750        | 9,0±1,0  |
|                 | 6            | 180        | 70 | M-24 | 136 | 2500        | 11,0±1,5 |
|                 | 7            | 205        | 75 | M-24 | 136 | 3500        | 12,0±2,0 |
| DURETE 60 SHORE |              |            |    |      |     |             |          |
| <b>S-B</b>      | 00B          | 60         | 18 | M-10 | 80  | 200         | 2,0±0,5  |
|                 | 0B           | 70         | 20 | M-12 | 100 | 350         | 2,0±0,5  |
|                 | 1B           | 85         | 25 | M-12 | 100 | 600         | 2,2±0,5  |
|                 | 2B           | 100        | 20 | M-14 | 110 | 800         | 2,5±0,5  |
|                 | 3B           | 120        | 25 | M-16 | 120 | 1100        | 2,5±0,5  |
|                 | 4B           | 140        | 33 | M-16 | 120 | 2000        | 3,5±0,5  |
|                 | 5B           | 160        | 31 | M-16 | 120 | 3000        | 4,0±1,0  |
| DURETE 75 SHORE |              |            |    |      |     |             |          |
| <b>AS</b>       | AS4020-60SH  | 40         | 20 | M-08 | 40  | 90          | 4,0±0,5  |
|                 | AS5020-45SH  | 52         | 20 | M-10 | 70  | 180         | 4,0±1,0  |
|                 | AS6020-60SH  | 52         | 20 | M-10 | 70  | 275         | 4,0±1,0  |
|                 | AS6520-75SH  | 52         | 20 | M-12 | 90  | 750         | 4,0±1,0  |
|                 | AS7526-60SH  | 69         | 26 | M-12 | 80  | 330         | 5,0±1,0  |
|                 | AS8026-75SH  | 69         | 26 | M-12 | 80  | 550         | 5,0±1,0  |

