

## AMORTIGUADORES ANTIVIBRATORIOS SILENTBLOCK\*\*TOPES DE GOMA\*\*TH

	REF / ART.NR		DIMENSIONES				COMPRESIÓN	
		Sh	ØA	B	D	i	CARGA	FLECHA
			mm.				kg.	mm.
TH	TH1610	60	16	10	M-05	5	20	1,5±0,5
	TH1615	60	16	15	M-05	5	15	2,5±0,5
	TH1620	60	16	20	M-05	5	15	3,5±1,0
	TH1625	60	16	25	M-05	5	15	4,5±1,0
	TH2008	60	20	8	M-06	5	45	1,6±0,5
	TH2015	60	20	15	M-06	5	35	3,0±0,5
	TH2020	60	20	20	M-06	5	25	4,0±1,0
	TH2025	60	20	25	M-06	5	25	5,0±1,0
	TH2030	60	20	30	M-06	5	25	6,0±1,0
	TH2510	50	25	10	M-08	6	50	2,0±0,5
	TH2515	50	25	15	M-08	6	40	3,0±0,5
	TH2520	50	25	20	M-08	6	40	4,0±0,5
	TH2525	50	25	25	M-08	6	40	5,0±1,0
	TH2530	50	25	30	M-08	6	40	6,0±1,0
	TH2540	50	25	40	M-08	6	40	8,0±1,0
	TH2822	50	28	22	M-08	6	60	5,0±1,0
	TH3010	50	30	10	M-08	6	80	2,0±0,5
	TH3015	50	30	15	M-08	6	80	3,0±0,5
	TH3020	50	30	20	M-08	6	80	4,0±0,5
	TH3030	50	30	30	M-08	6	60	6,0±1,0
	TH3040	50	30	40	M-08	6	60	8,0±1,0
	TH4020M8	50	40	20	M-08	6	140	4,0±0,5
	TH4020	50	40	20	M-10	7	140	4,0±0,5
	TH4028M8	50	40	28	M-08	6	100	5,5±1,0
	TH4028	50	40	28	M-10	7	100	5,5±1,0
	TH4035	50	40	35	M-10	7	100	7,0±1,0
	TH4040M8	50	40	40	M-08	6	100	8,0±1,0
	TH4040	50	40	40	M-10	7	100	8,0±1,0
	TH4045	50	40	45	M-10	7	90	9,0±1,0
	TH5020	50	50	20	M-10	7	300	4,0±0,5
	TH5025	50	50	25	M-10	7	175	5,0±1,0
	TH5030	50	50	30	M-10	7	160	6,0±1,0
	TH5035	50	50	35	M-10	7	160	7,0±1,0
	TH5040	50	50	40	M-10	7	155	8,0±1,0
	TH5045	50	50	45	M-10	7	150	9,0±1,0
	TH5060	50	50	60	M-10	7	130	12,0±1,5
	TH6025	50	60	25	M-10	7	400	5,0±1,0
	TH6035	50	60	35	M-10	7	300	7,0±1,0
	TH6045	50	60	45	M-10	7	250	9,0±1,0
	TH6060	50	60	60	M-10	7	225	12,0±1,5
	TH7035M10	50	70	35	M-10	9	450	7,0±1,0
	TH7040M10	50	70	40	M-10	9	400	8,0±1,0
	TH7050M10	50	70	50	M-10	9	300	10,0±1,0
	TH7070M10	50	70	70	M-10	9	300	14,0±1,5
	TH7035	50	70	35	M-12	10	450	7,0±1,0
TH7040	50	70	40	M-12	10	400	8,0±1,0	
TH7050	50	70	50	M-12	10	300	10,0±1,0	
TH7070	50	70	70	M-12	10	300	14,0±1,5	
TH8030	50	80	30	M-14	9	950	6,0±1,0	
TH8040	50	80	40	M-14	9	600	8,0±1,0	
TH8055	50	80	55	M-14	9	500	11,0±1,5	
TH9525	60	95	25	M-16	14	1800	5,0±1,0	
TH9540	50	95	40	M-16	14	1000	8,0±1,0	

