



TP\_EN

	REF / ART.NR		DIMENSIONS				COMPRESSION		SHOCK	
		Sh	ØA	B	D	C	LOAD	DEFLECTION	LOAD	DEFLECTION
			mm.				kg.	mm.	kg.	mm.
TP-1	TP25	60	25	20	M-08	20	40	4,0±0,5	100	8,0±2,0
	TP30	60	30	30	M-06	15	50	6,0±1,0	140	12,0±2,0
	TP30M8X20	60	30	30	M-08	20	50	6,0±1,0	140	12,0±2,0
	TP5050M8X20	60	50	50	M-08	20	90	10,0±1,5	335	20,0±3,0
	TP5050M10	60	50	50	M-10	25	90	10,0±1,5	335	20,0±3,0
	TP5058M8X20	60	50	58	M-08	20	90	12,0±2,0	370	23,0±3,0
	TP5058M10	60	50	58	M-10	25	90	12,0±2,0	370	23,0±3,0
	TP5065M8X20	60	50	65	M-08	20	90	13,0±2,0	370	26,0±4,0
	TP5065M10	60	50	65	M-10	25	90	13,0±2,0	370	26,0±4,0
	TP70	60	70	60	M-12	33	160	12,0±2,0	550	24,0±3,0
TP-2	TP95	60	95	80	M-16	42	350	16,0±2,0	1100	32,0±4,0
	TP85	60	84	53	M-12	33	375	11,0±2,0	1250	21,0±2,5
	TP96	60	95	47	M-16	42	675	9,0±1,0	1600	19,0±2,0
	TP120	75	120	75	M-16	42	2000	15,0±2,0	4500	30,0±4,0
	TP220	60	220	136	M-24	80	3800	27,0±3,0	10000	54,0±6,0

TP-1



TP-2



TP-96

